## AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Comte 8 🔺 CH-1844 Villeneuve 🔺 +41 (0)2) 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



## Harness inspection certificate - NfL

Inspection certificate number: PH\_351.2022 Impact pad number: PH\_351.2022

## Manufacturer data

Manufacturer name: Supair SAS
Representative: Laurent Chiabaut

Street: Parc Altais / 34, rue Adrastée

Post code / place: 74650 Chavanod

Country: France

Sample data:	Harness		Impact pad
Name:	Radical 4	Name Impact pad: (1)	Module Radical 4
Type:	ABS	Impact pad integrated: (1)	No
Size:	М	Impact pad type:	Airbag
Weight of Sample [kg]:	2.12	Weight of Sample [kg]: (1)	1.12
Serial number:	RAD4-M-PS	Serial number: <sup>(1)</sup>	BRAD4-M-PS4
Clip-in weight [kg]:	120		
Integrated container for rescue system:	Yes	Date of reception:	07.12.2021
Volume container [cm <sup>3</sup> ]:	4	700 max	
	3	300 min	
Date of reception:	07.12.2021		

Test report summary	Structual test	Impact pad test	
Result	POSITIVE	POSITIVE	
Place	Villeneuve	Villeneuve	
Date	11.01.2022	07.01.2022	

## Issue data

Place of declaration: Villeneuve
Date of issue: 05.04.2022
Managing Director: Andrea Wigger

Signature:

This signature approves the validity of the test reports if available; no. 94.21 (test id 02, 03, 13, 09, 04, 14, 07) and no. 94.22 (test id: P, PR)

Air Turquoise SA, having thoroughly assessed the sample mentioned above, declares it was found conform with all requirements defined by the following norms:

Airworthiness Requirements NfL 2-565-20 - EN12491:2015 5.3.2

Present declaration's scope only extends to the conformity of a given sample, on a given date and in a given place – as mentioned here above.

This inspection certificate contains the following test and is complet with the test, if available, report: 94.21 and 94.22

<sup>(1)</sup> If Impact pad is NOT integrated in the harness, it will have independently Inspection number, and serial number. Definition of integrated impact pad is impact pad which can not be dismounted from the harness, e.g. airbag. (2) If harness has an integrated inner container for emergency parachute, extra deployment tests are done for different type of emergency parachute.